

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>B01D 53/94, F01N 3/02, 3/08, 3/20</b>		A1	(11) International Publication Number: <b>WO 00/21647</b>
			(43) International Publication Date: 20 April 2000 (20.04.00)
(21) International Application Number: PCT/GB99/03281		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 4 October 1999 (04.10.99)			
(30) Priority Data: 9822083.3 ✓ 12 October 1998 (12.10.98) GB 9917042.5 ✓ 21 July 1999 (21.07.99) GB			
(71) Applicant (for all designated States except US): JOHNSON MATTHEY PUBLIC LIMITED COMPANY [GB/GB]; 2-4 Cockspur Street, Trafalgar Square, London SW1Y 5BQ (GB).			
(72) Inventor; and (75) Inventor/Applicant (for US only): TWIGG, Martyn, Vincent [GB/GB]; 108 Ermine Street, Caxton, Cambridge CB3 8PQ (GB).			
(74) Agent: WISHART, Ian, Carmichael; Johnson Matthey Technology Centre, Blounts Court, Sonning Common, Reading RG4 9NH (GB).		Published With international search report.	

(54) Title: PROCESS AND APPARATUS FOR TREATING COMBUSTION EXHAUST GAS

(57) Abstract

A system and method for the control of emissions from a diesel engine exhaust, comprises a catalyst (14) to convert NO to NO<sub>2</sub>, a filter (16) to trap soot and hold it for combustion with the NO<sub>2</sub>, and a NO<sub>x</sub> absorber (28), with means to regenerate the NO<sub>x</sub> absorber by injecting reductant or other reactant (injector 18) upstream of the absorber, and at least during regeneration, passing the exhaust gases leaving the absorber through a three-way catalyst (30).

